


FormsPro 4000 Series




Other Features

Options and accessories include: 240 VAC, 50 Hz power supply, IBM twinax, coax and IPDS interfaces, Ether-Link interface, FormsCutter, printstand, and Imager and ImagerPlus bar code support.



An optional printstand features a paper guide which helps steer long reports into the rear catch basket.



The 4503's unique Tri-Trak paper handling system keeps three forms loaded at all times.

Printek and the Printek logo are registered trademarks of Printek, Inc. Centronics is a trademark of Centronics Data Computer Corp. DEC is a registered trademark of Digital Equipment Corp. Epson is a registered trademark of Seiko Epson Corp. FX is a registered trademark of Epson America, Inc. IBM is a trademark of International Business Machines.



Specifications

Print Modes	4500/4503	4300
Fast Draft	530 cps	300 cps
Draft	400 cps	225 cps
Fast Draft/High Impact	265 cps	150 cps
High Impact	200 cps	110 cps
Letter Quality	100 cps	55 cps
Optical Quality	65 cps	38 cps
Graphics*	15,360 dps	8,640 dps

Character Matrix

Fast Draft: 9 x 9 cell
Draft: 12 x 9 cell
Letter Quality: 24 x 18 cell
Optical Quality: 36 x 18 cell

Printhead

18 wire parallel array.

Character Sets

Fast Draft, Draft and Letter Quality for Epson and IBM Proprinter. Optical Quality for OCR-A and OCR-B.

Character Spacing

5, 6, 6.7, 7.5, 8.4, 8.6, 10, 12, 13.3, 15, 16.7, 17.1 and 20 cpi.

Line Length

13.6 inches (34.5 cm).

Line Spacing

6 and 8 lpi. Also software programmable.

Paper Handling

Tear Bar: Auto-Scroll allows zero tear-off distance.
Auto-Gap: Adjusts printhead to form thickness.
Paper Type: Fanfold, continuous forms, edge punched, 15 lb. minimum weight for single-part paper.
Sensing: Paper motion, paper edge and paper out.

Operator Controls

Normal Operating Mode: Online, Form Feed/Load, Form Select/Unload and Vertical Print Adjustment.

Form Parameters

Non-volatile memory for ten forms, each supporting settings for: tractor path, cpi, lpi, form length, left and right margins, top and bottom margins, unidirectional printing, slashed or non-slashed zero, language, font, high-impact on/off.

Operator Indicators

LEDs for Power, Online and Fault; 1 x 16 LCD for form selection; on/off line status and error descriptions.

Ribbon

Cartridge: nylon fabric, mobius loop, 23 million characters.

Power Requirements

Voltage: 120 VAC \pm 10%
Frequency: 60 Hz
Power Consumption: 60W non-printing, 225W printing. Optional 240 VAC, 50 Hz power supply also available.

Paper Slew Rate

12 ips.

Paper Width

2.5" to 15" (6.4 cm to 38.1 cm).

Paper Loading

Straight path, bottom loading.

Multi-part Forms

1 to 9 parts; 0.025" max. thickness.

Graphics Density*

60 to 240 dpi horizontally x 72 dpi vertically.

Audible Noise (Draft Mode)

62 dBA.

Setup (Automatic Methods)

Printer-to-printer or setup unit.

I/O Buffer

4k, expandable to 28k.

Standard Interfaces

Parallel: Centronics compatible.
Serial: RS232, 300 to 19,200 baud.

Optional Interfaces

Twinax, Coax, IPDS and Ethernet.

Software Controls

Emulation choice of Printek, Epson FX, IBM Proprinter, DEC LA120 or Basic Bar Codes (Includes Code 39, 2 of 5, Interleaved 2 of 5).

Physical Specifications

H x W x D: 9.5" x 25" x 20.3"
 (24 cm x 63.5 cm x 51.5 cm)

Weight: 53 lbs. (28 kg)

Reliability

MTBF: 10,000 hours on electronics with no duty cycle limitations.

Printhead Life: 500 million draft equivalent characters.

Warranty: One-year printer warranty, two-year limited printhead warranty when Printek brand ribbons are used; one-year warranty when non-Printek brand ribbons are used.

*May be emulation dependent.

MidWest Technology Services Inc · 531W · Wrightwood Ave · Elmhurst · IL · 60126 · MTSPrinters.com
 For information on Supplies, Products or Services Please Contact us Ph: 630.782.9494 Fx: 630.782.9095